

FIRECLIP™


DATA SHEET



DIRECTIONS FOR USE


Our FireClips are designed specifically for soft skin, flex and round cabling. They are suitable for all substrates.

Installation could not be simpler.



Drill a 6mm hole

Your pack of clips will carry instructions on the recommended diameter of drill bit required for your chosen clip.



Slide the clip over the cable

When sliding the clip over the cable, ensure that it is seated into the rounded area.



Compress the clip & insert into the hole

The clips can be easily compressed by hand. Squeeze the clip legs and simply insert it into the hole.

TESTING AND COMPLIANCE

>1000°C melting point

Meets 90 minute fire time in accordance with DIN4102-12

Meets 120 minute fire time in accordance with BSEN50200

Compliant with the requirements of BS 8519:2010

Salt spray tested to 500 hours

Smoke emission tested to London Underground Standard

Supports tensile loads of 24kg*

Life saver - meets recommendations for

Fire Rated Cable Fixings BS7671 18th Edition



*Average achieved in C35 Grade Concrete

T. +44 (0) 141 465 4858

E. info@linianclip.co.uk

Visit our website to find your nearest stockist

WWW.LINIANCLIP.CO.UK



Next generation
safety, efficiency
& value.

Check out our website to discover the full range of LINIAN Clips, designed for all your needs.

LINIAN FIRECLIP SIZE CHART

PART NUMBER	PART DESCRIPTION	SUITABLE FOR	OVERALL DIAMETER	CC EQUIVALENT
1LCR608	LINIAN FireClip Single (RED)	Round Cable	6mm – 8mm	CC4
1LCR911	LINIAN FireClip Single (RED)	Round Cable	9mm – 11mm	CC5
1LCR682	LINIAN FireClip Double (RED)	Round Cable X2	6mm – 8mm (X2 Side by Side)	CC4 (X2)
1LCR9112	LINIAN FireClip Double (RED)	Round Cable X2	9mm – 11mm (X2 Side by Side)	CC5 (X2)
1LCW608	LINIAN FireClip Single (WHITE)	Round Cable	6mm – 8mm	CC4
1LCW911	LINIAN FireClip Single (WHITE)	Round Cable	9mm – 11mm	CC5
1LCW682	LINIAN FireClip Double (WHITE)	Round Cable X2	6mm – 8mm (X2 Side by Side)	CC4 (X2)
1LCW9112	LINIAN FireClip Double (WHITE)	Round Cable X2	9mm – 11mm (X2 Side by Side)	CC5 (X2)
1LCB608	LINIAN FireClip Single (BLACK)	Round Cable	6mm – 8mm	CC4
1LCB911	LINIAN FireClip Single (BLACK)	Round Cable	9mm – 11mm	CC5
1LCB682	LINIAN FireClip Double (BLACK)	Round Cable X2	6mm – 8mm (X2 Side by Side)	CC4 (X2)
1LCB9112	LINIAN FireClip Double (BLACK)	Round Cable X2	9mm – 11mm (X2 Side by Side)	CC5 (X2)

Recommended Spacing: 300mm
Hole Diameter: 6mm*
Hole Depth: 30mm

34-38 Payne Street
Port Dundas Trading Estate
Glasgow G4 0LF, UK
Tel: +44 (0)141 465 4858
Email: info@linianclip.co.uk

* Varies for best fixing according to substrate

SUPERCLIP™


DATA SHEET



DIRECTIONS FOR USE


Our SuperClips are designed specifically for conduit, armoured and grouped cables. They are suitable for all substrates.

Installation could not be simpler.



Drill a 10mm hole

Your pack of clips will carry instructions on the recommended diameter of drill bit required for your chosen clip.



Slide the clip over the cable

When sliding the clip over the cable, ensure that it is seated into the rounded area.



Compress the Clip & insert into the hole

The clips can be easily compressed by hand. Squeeze the clip legs and simply insert it into the hole.

TESTING AND COMPLIANCE

>1000oC melting point

Meets 90 minute fire time in accordance with DIN4102-12

Meets 120 minute fire time in accordance with BSEN50200

Compliant with the requirements of BS 8519:2010

Salt spray tested to 500 hours

Smoke emission tested to London Underground Standard

Supports tensile loads of 44kg*

Life saver - meets recommendations for

Fire Rated Cable Fixings BS7671 18th Edition



*Average achieved in C35 Grade Concrete

T. +44 (0) 141 465 4858

E. info@linianclip.co.uk

Visit our website to find your nearest stockist

WWW.LINIANCLIP.CO.UK

Check out our website to discover the full range of LINIAN Clips, designed for all your needs.

LINIAN SUPERCLIP SIZE CHART

PART NUMBER	PART DESCRIPTION	SUITABLE FOR	OVERALL DIAMETER	CC EQUIVALENT
1LSB1214	12-14mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables	Max. 14mm	CC6
1LSB1518	15-18mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables	Max. 18mm	CC7
1LSB1820	18-20mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables	Max. 20mm	CC8
1LSB2022	20-22mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 22mm	CC9
1LSB2325	23-25mm LINIAN SuperClip (BLACK)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 25mm	CC10
1LSW1214	12-14mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables	Max. 14mm	CC6
1LSW1518	15-18mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables	Max. 18mm	CC7
1LSW1820	18-20mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables	Max. 20mm	CC8
1LSW2022	20-22mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 22mm	CC9
2LSW2325	23-25mm LINIAN SuperClip (WHITE)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 25mm	CC10
1LSR1214	12-14mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables	Max. 14mm	CC6
1LSR1518	15-18mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables	Max. 18mm	CC7
1LSR1820	18-20mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables	Max. 20mm	CC8
1LSR2022	20-22mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 22mm	CC9
2LSR2325	23-25mm LINIAN SuperClip (RED)	Heavy Round Cable/ Bunched Cables/Conduit	Max. 25mm	CC10

Recommended Spacing: 300mm
Hole Diameter: 10mm*
Hole Depth: 40mm

34-38 Payne Street
Port Dundas Trading Estate
Glasgow G4 0LF, UK
Tel: +44 (0)141 465 4858
Email: info@linianclip.co.uk

* Varies for best fixing according to substrate

LINIAN 
FASTER. SAFER. SIMPLER.

Visit our website to find your nearest stockist
WWW.LINIANCLIP.CO.UK

T&E CLIP™


DATA SHEET



DIRECTIONS FOR USE

Our T&E Clips are designed specifically for flat twin and cpc cabling (twin and earth) and are suitable for all substrates.

Installation could not be simpler.



Drill a 6mm hole

Your pack of clips will carry instructions on the recommended diameter of drill bit required for your chosen clip.



Slide the clip over the cable

When sliding the clip over the cable, ensure that it is seated into the rounded area.



Compress the Clip & insert into the hole

The clips can be easily compressed by hand. Squeeze the clip legs and simply insert it into the hole.

TESTING AND COMPLIANCE

>1000oC melting point

Meets 90 minute fire time in accordance with DIN4102-12

Meets 120 minute fire time in accordance with BSEN50200

Compliant with the requirements of BS 8519:2010

Salt spray tested to 500 hours

Smoke emission tested to London Underground Standard

Supports tensile loads of 24kg

Life saver - meets recommendations for

Fire Rated Cable Fixings BS7671 18th Edition



*Average achieved in C35 Grade Concrete

T. +44 (0) 141 465 4858

E. info@linianclip.co.uk

Visit our website to find your nearest stockist

WWW.LINIANCLIP.CO.UK



Next generation
safety, efficiency
& value.

Check out our website to discover the full range of LINIAN Clips, designed for all your needs.

LINIAN T&E CLIP SIZE CHART

PART NUMBER	PART DESCRIPTION	SUITABLE FOR	OVERALL DIAMETER
1LTEG001	1mm LINIAN Twin & Earth Clip (GREY)	Flat Cable	7mm x 4mm
1LTEG001.5	1.5mm LINIAN Twin & Earth Clip (GREY)	Flat Cable	9mm x 5mm
1LTEG002.5	2.5mm LINIAN Twin & Earth Clip (GREY)	Flat Cable	10mm x 5mm
1LTEG004	4mm LINIAN Twin & Earth Clip (GREY)	Flat Cable	13mm x 6mm
1LTEG006	6mm LINIAN Twin & Earth Clip (GREY)	Flat Cable	14mm x 7mm
1LTEG010	10mm LINIAN Twin & Earth Clip (GREY)	Flat Cable	18mm x 9mm
1LTEW001	1mm LINIAN Twin & Earth Clip (WHITE)	Flat Cable	7mm x 4mm
1LTEW001.5	1.5mm LINIAN Twin & Earth Clip (WHITE)	Flat Cable	9mm x 5mm
1LTEW002.5	2.5mm LINIAN Twin & Earth Clip (WHITE)	Flat Cable	10mm x 5mm
1LTEW004	4mm LINIAN Twin & Earth Clip (WHITE)	Flat Cable	13mm x 6mm
1LTEW006	6mm LINIAN Twin & Earth Clip (WHITE)	Flat Cable	14mm x 7mm
1LTEW010	10mm LINIAN Twin & Earth Clip (WHITE)	Flat Cable	18mm x 9mm

Recommended Spacing: 300mm
Hole Diameter: 6mm*
Hole Depth: 30mm

34-38 Payne Street
Port Dundas Trading Estate
Glasgow G4 0LF, UK
Tel: +44 (0)141 465 4858
Email: info@linianclip.co.uk

* Varies for best fixing according to substrate

LINIAN 
FASTER. SAFER. SIMPLER.

Visit our website to find your nearest stockist

WWW.LINIANCLIP.CO.UK